

PB TOP SERIES
SCISSOR LIFTS

PLATFORMERS
BUSINESS

PB TOP 12

Working height:
15,08 m - 22,50 m

Width:
1,22 m

Drive:
Electro-hydraulic



Technical highlights in series

- No space? no problem:
Slim + extremely high
- Autom. PB supports
system
 - Differential lock
- Emission-free & eco-
friendly & reliable



PB TOP 12 SERIES

8 types

Working height:
15,08 m - 22,50 m

Width:
1,22 m

Drive:
Electro-hydraulic



PB Liftechnik GmbH
Gewerbegebiet Gassenäcker

Phone +49 (0) 90 77 - 95 00 - 0

E-Mail: info@pblift.de
Website: www.pblift.de



PB TOP 12 series	PB S151-12E	PB S151-12ES	PB S171-12E	PB S171-12ES
Operation area	Indoor	In-/outdoor	Indoor	In-/outdoor
Drive	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Working height	15,08 m	15,30 m	17,30 m	17,30 m
Platform height - raised	13,08 m	13,30 m	15,30 m	15,30 m
Drivable at full height	Yes	Yes	Yes	Yes
Drive speed stowed / raised	2,4 / 0,14 km/h	2,4 / 0,14 km/h	2,4 / 0,14 km/h	2,4 / 0,14 km/h
Platform size (l x w)	2,90 x 1,19 m	2,90 x 1,19 m	2,90 x 1,19 m	2,90 x 1,19 m
Platform size max. (l x w)	3,90 x 1,19 m	3,90 x 1,19 m	3,90 x 1,19 m	3,90 x 1,19 m
Lift capacity	600 kg	600 kg	500 kg	500 kg
Lift capacity extension	600 kg	600 kg	500 kg	500 kg
Occupancy (in-/outdoor)	2/-	2/2	2/-	2/2
Weight	5520 kg	5360 kg	5180 kg	5680 kg
Total length	3,00 m	3,28 m	3,00 m	3,28 m
Total width	1,22 m	1,22 m	1,22 m	1,22 m
Total height - stowed	2,96 m	2,96 m	3,14 m	3,14 m
Transport height (rails folded)	2,15 m	2,15 m	2,33 m	2,33 m
Turning radius - outside	2,83 m	3,14 m	2,83 m	3,14 m
Ground clearance - center	0,27 m	0,27 m	0,27 m	0,27 m
Gradeability	25 %	25 %	25 %	25 %
Perm. tilt angle (long-/lat. axis)	1,5°/1,5°	1,5°(0,3°supp.)	1,5°/1,5°	1,5°(0,3°supp.)
Motor	8 kW 48V	8 kW 48V	8 kW 48V	8 kW 48V
Battery capacity	336Ah5 Aqua.	336Ah5 Aqua.	336Ah5 Aqua.	336Ah5 Aqua.

Technical data are subject to change.

PB TOP 12 series	PB S195-12E	PB S195-12ES	PB S225-12E	PB S225-12ES
Operation area	Indoor	In-/outdoor	Indoor	In-/outdoor
Drive	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Working height	19,60 m	19,60 m	22,50 m	22,50 m
Platform height - raised	17,60 m	17,60 m	20,50 m	20,50 m
Drivable at full height	Yes	Yes	Yes	Yes
Drive speed stowed / raised	1,63 / 0,10 km/h	1,63 / 0,10 km/h	1,63 / 0,10 km/h	1,63 / 0,10 km/h
Platform size (l x w)	3,82 x 1,19 m	3,82 x 1,19 m	3,98 x 1,19 m	3,98 x 1,19 m
Platform size max. (l x w)	5,32 x 1,19 m	5,32 x 1,19 m	5,48 x 1,19 m	5,48 x 1,19 m
Lift capacity	700 kg	700 kg	600 kg	600 kg
Lift capacity extension	700 kg	700 kg	600 kg	600 kg
Occupancy (in-/outdoor)	2/-	2/2	2/-	2/2
Weight	ca. 9650 kg	9950 kg	ca. 10000 kg	10290 kg
Total length	4,18 m	4,51 m	4,18 m	4,52 m
Total width	1,22 m	1,22 m	1,22 m	1,22 m
Total height - stowed	3,46 m	3,46 m	3,57 m	3,57 m
Transport height (rails folded)	2,45 m	2,45 m	2,73 m	2,73 m
Turning radius - outside	3,65 m	3,65 m	3,65 m	3,65 m
Ground clearance - center	0,27 m	0,27 m	0,27 m	0,27 m
Gradeability	25 %	25 %	25 %	25 %
Perm. tilt angle (long-/lat. axis)	1,5°/1,5°	1,5°(0,3°supp.)	1,5°/1,5°	1,5°(0,3°supp.)
Motor	2x 8 kW 48V	2x 8 kW 48V	2x 8 kW 48V	2x 8 kW 48V
Battery capacity	640Ah5 Aqua.	640Ah5 Aqua.	640Ah5 Aqua.	640Ah5 Aqua.

Technical data are subject to change.

Technical highlights in series

- No space? no problem:
Slim + extremely high
- Autom. PB supports system
 - Differential lock
- Emission-free & eco-friendly & reliable



www.pblift.de