PB TOP SERIES
SCISSOR LIFTS

PB S190-23ESP 4x4
PB S225-23ESP 4x4

Working height:
19,49 m / 22,41 m

Width:
2,31 m

Drive:
Electro-hydraulic
or
Diesel-hydraulic



PLATFORMERS
BUSINESS

Technical highlights in series

- Strong & big & safe
- PB Mega Deck
- 4-wheel drive
- 2-axis steering
- Autom. Supports system
- Differential lock

PB PLATFORMS

www.pblift.de

PB TOP SERIES

PB S190-23ESP 4x4
PB S225-23ESP 4x4

Working height:
19,49 m / 22,41 m

Width:
2,31 m

Drive:
Electro-hydraulic
or
Diesel-hydraulic

PB PLATFORMS

PB Lifttechnik GmbH
Gewerbegebiet Gassenäcker

Tel. +49 (0) 90 77 - 95 00 - 0

E-Mail: info@pblift.de
Website: www.pblift.de

PB TOP series	PB S190-23ESP 4x4	PB S225-23ESP 4x4
Operation area	In-/+outdoor	In-/+outdoor
Drive	Electro-hydraulic	Electro-hydraulic
Alternative Diesel Version	-	PB S225-23DSP 4x4
Working height	19,49 m	22,41 m
Platform height - raised	17,49 m	20,41 m
Drivable at full height	Yes	Yes
Drive speed stowed / raised	5,4 / 0,50 km/h	5,4 / 0,50 km/h
Platform size (l x w)	4.50 x 2.22 m	4.50 x 2.22 m
Platform size max. (l x w)	7.20 x 2.22 m	7.20 x 2.22 m
Lift capacity	1200 kg	1000 kg
Lift capacity extension	1200 kg	1000 kg
Occupancy (in-+/outdoor)	4/4	4/4
Weight	15000 kg	15650 kg
Total length	4,95 m	4,95 m
Total width	2,31 m	2,31 m
Total height - stowed	3,66 m	3,92 m
Transport height (rails folded)	2,82 m	3,07 m
Turning radius (inside / outside)	0,52 m / 3,40 m*	0,52 m / 3,40 m*
Ground clearence - center	0,39 m	0,39 m
Gradeability	30 %	30 %
Perm. tilt angle (long-/lat. axis)	3°(0,3°supp.)	3°(0,3°supp.)
Battery capacity	625 Ah	625 Ah

Technical data are subject to change. *With 2-axis steering

Technical highlights in series

- Strong & big & safe
- PB Mega Deck: Huge workspace
- 4-wheel-drive
- 2-axis-steering
- Auto. Supports system
- Differential lock











www.pblift.de